LOW PROFILE DIFFUSER (AIRELIGHT™ LINEAR SC)





DESCRIPTION

When combined with the AirelightTM Linear SC 1.0, the Low Profile Diffuser provides a modern, streamlined aesthetic to an already lambertian output. Available in lengths from 2'-10' and simple to install, the Low Profile Diffuser delivers a pleasing, seamless line of light. The AirelightTM Linear SC 1.0 with Low Profile Diffuser delivers up to 670 lumens/ft with an impressive 87% lens efficiency.

SPECIFICATIONS

Material	Diffuser: Polycarbonate / Endcaps (2): Anodized Aluminum
Part Number	11319
Beam Angle	Lambertian
Lens Efficiency	87%
Dimensions	W 1.02" x 0.36" x L (2'-10')
Warranty	5 Years

AIRELIGHT™SC 1.0 W/ LOW PROFILE DIFFUSER

Lumens Per Foot 670 @ 4000K / 660 @ 3500K / 660 @ 3000K / 600 @ 2700K

Efficacy (lms/W) 112 @ 4000K / 110 @ 3500K / 110 @ 3000K / 100 @ 2700K

CRI 83 @ 4000K / 84 @ 3500K / 83 @ 3000K / 82 @ 2700K

.36"

TECHNICAL DRAWING

1.02"

